






ACTUAL SIZE

* POSITION OF IMU CENTER




SCALE 2:1



 INERTIAL SENSE autonomous navigation solutions	PRODUCT RUG-3-IMX-5-DUAL					
	PART INFORMATION P/N: IS-RUG-3.0-G2					
TOLERANCES UNLESS OTHERWISE SPECIFIED: LINEAR DIMENSIONS: ±.005 ANGULAR DIMENSION: ±0.5°		DIMENSIONS AND PINOUT				
ALL DIMENSIONS IN INCHES						
APPROVED	WALT JOHNSON	8/11/22	SIZE	MATERIAL	DWG NO	REV
CHECKED	ANDREW PRIDDIS	8/11/22	A		IS-RUG-3.0-G2-PINOUT	1
DRAWN	ANDREW PRIDDIS	8/9/22	SCALE 1:1	WEIGHT	SHEET 1/2	

▽

"MAIN" CONNECTOR PINOUT (ON RUGGED SIDE, NOT CABLE SIDE)



PIN	NAME	DIRECTION	DESCRIPTION
1	GND	PWR	Common Ground
2	G9/STROBE	I/O	Strobe time sync input. (Includes 390 ohm series resistor)
3	VIN	PWR	4V - 20V system supply input
4	USB.D+	I/O	USB data positive line
5	GPS PPS	O	GPS time synchronization output pulse (1Hz, 10% duty cycle)
6	USB.D-	I/O	USB data negative line
7	G3/TX0/485TX2-/SCLK	I/O	Serial 0 output (TTL or RS232) Serial 2 output- (RS485) SPI - SCLK
8	G2/TX2/485TX2+/MISO	I/O	Serial 2 output (TTL or RS232) Serial 2 output+ (RS485/RS422) SPI - MISO
9	G4/RX0/485RX2-/CS	I/O	Serial 0 input (TTL or RS232) Serial 2 input- (RS485/RS422) SPI - CS
10	G1/RX2/485RX2+/MOSI	I/O	Serial 2 input (TTL or RS232) Serial 2 input+ (RS485/RS422) SPI - MOSI
11	G1/CANL/RX2	I/O	High level (CAN bus) Serial 2 input (TTL)
12	G2/CANH/TX2/STROBE	I/O	Low level (CAN bus) Serial 2 output (TTL) Strobe time sync input.



INERTIAL SENSE
autonomous navigation solutions

TOLERANCES
UNLESS OTHERWISE SPECIFIED:

LINEAR DIMENSIONS: ±.005
ANGULAR DIMENSION: ±0.5°

ALL DIMENSIONS IN INCHES

PRODUCT

RUG-3-IMX-5-DUAL

PART INFORMATION

P/N: IS-RUG-3.0-G2

DIMENSIONS AND PINOUT

APPROVED	WALT JOHNSON	8/11/22	SIZE	MATERIAL	DWG NO	REV
CHECKED	WALT JOHNSON	8/11/22	A		IS-RUG-3.0-G2-PINOUT	1
DRAWN	ANDREW PRIDDIS	8/9/22	SCALE	WEIGHT	SHEET 2/2	

